## 1. A surface S is parametrized by

$$\mathbf{r}(u,v) = < u^2, uv, v >$$

where (u, v) are in the triangular region bounded by the u- and v-axes and the line u + 2v = 4.

## Express

$$\iint_{S} (x - y^2) \, dS$$

as an iterated integral that would have made sense to you at the time of your last midterm exam. **DO NOT EVALUATE** the integral.

$$\vec{v}_{u} = \langle 2u, v, o \rangle$$

$$\vec{v}_{v} = \langle 0, u, 1 \rangle$$

$$\vec{v}_{u} \times \vec{v}_{v} = \langle v, -2u | 2u^{2} \rangle$$


$$||\vec{v}_{u} \times \vec{v}_{v}|| = \int \vec{v}_{v}^{2} + 4u^{2} + 4u^{4}$$

$$\int (x-y^{2})dS = \int (u^{2}-u^{2}v^{2}) \sqrt{v^{2}+4u^{2}+4u^{4}} du dv$$

$$\int (u^{2}-u^{2}v^{2}) \sqrt{v^{2}+4u^{2}+4u^{4}} dv du$$

$$\int (u^{2}-u^{2}v^{2}) \sqrt{v^{2}+4u^{2}+4u^{4}} dv du$$

2. Give a parameterization of the cylindrical surface obtained by moving a circle of radius 2 in the xz-plane, centered at the origin, in the y-direction from y=0 to y=4. Be sure you both supply a formula for the parameterizing function, and indicate the values the parameters range over.



£ .